

DURABILITY & DEPENDABILITY



DeKa[®]

D-Series[™]

MOTIVE POWER BATTERIES

QUALITY SYSTEM
CERTIFIED
ISO 9001
ISO/TS 16949
ENVIRONMENTAL
SYSTEM CERTIFIED
ISO 14001

 **EASTPENN**



MADE IN U.S.A.
WITH U.S. AND
IMPORTED MATERIALS



D-Series

Decrease downtime and raise profitability with **DEKA INDUSTRIAL MOTIVE POWER BATTERIES**. Available in 35-160 Ah positive models, precision-built **DEKA BATTERIES** provide up to 2000 Ah (at a 6-hour rate) of dependable power for all your material handling needs.

Designed and manufactured with the finest materials under strict computer control, **DEKA INDUSTRIAL MOTIVE POWER BATTERIES** require fewer non-productive changeouts, reducing downtime. All **DEKA BATTERIES** pass through more than 250 quality control checks to assure consistent quality every time. And **DEKA BATTERIES** have the smallest percentage of warranty claims in the industry, substantially decreasing your cost-per-cycle and raising your productivity and profits.

DEKA INDUSTRIAL MOTIVE POWER BATTERIES are backed by a nationwide sales and service team, ready to handle all your industrial battery and charger repair and maintenance needs. Our highly skilled technicians come directly to your business site to conduct emergency repairs, preventative maintenance and routine inspections. This on-site service keeps your equipment up and running rather than sitting idle while batteries are sent out for repairs.

MODEL	AH POS	OVERALL HEIGHT		
		NO COVER	DOME COVER	FLAT COVER
D35	35	12-3/8"*	13"	13-1/4"
D45	45	14-7/8"*	15-1/2"	15-3/4"
D55	55	18-1/8"*	18-3/4"	19"
D65	65	20"*	20-5/8"	20-7/8"
D75	75	22-5/8"	23-1/4"	23-1/2"
D85	85	22-5/8"	23-1/4"	23-1/2"
D100	100	25-5/8"	26-1/4"	26-1/2"
D110	110	30-1/2"	31-1/8"	31-3/8"
D125	125	30-1/2"	31-1/8"	31-3/8"
D150	150	30-1/2"	31-1/8"	31-3/8"
D160	160	30-1/2"	31-1/8"	31-3/8"

* D35, D45, D55 and D65 available in reduced no-cover heights using drop handles. Refer to battery selector guide.

Compare these features which are standard on every Deka battery:

- East Penn uses exclusive formation processes that ensures optimized power capacity, cell consistency, and long term reliability from every plate and ultimately each cell, in terms of amp- hour capacity and cycle life.
- Superior non-porous, precision-cast grids are designed for maximum current-carrying capacity exclusively for motive power applications. The grids are pasted with active material that delivers reliable performance throughout a long service life. All phases of plate production are computer controlled to meet rigid quality control specifications.
- Both the positive and negative plates are cured in temperature/humidity-controlled ovens to ensure optimum plate curing regardless of external environmental conditions.
- The positive plate is protected by a multiple-step retention system, including two layers of vertical mats consisting of fiberglass tape and interwoven glass fibers, a horizontal glass fiber mat, and a perforated retainer envelope. This ensures optimum active material retention for longer life, and provides increased plate insulation for added performance. The positive plates are also surrounded by deep channeled, microporous separators that provide a durable barrier between positive and negative plates, while allowing the free flow of electrolyte throughout the cell, optimizing performance and extending service life.
- No other industrial battery manufacturer can claim these and other features, plus ensure the highest quality material, workmanship and superior engineering technology. All of these important components make the Deka name synonymous with number one quality in the production of precision-built batteries.
- Manufactured in compliance with American National Standards Institute and Underwriters Laboratories Standard Number ANSI/UL583.
- Federal Specification Number W-B-133D.
- Complies with Industrial Truck Association Recommended Practices.



e-mail: epmmotive@eastpenn-deka.com www.dekabatteries.com



East Penn Manufacturing Co. Lyon Station, PA 19536-0147 Phone: 610-682-6361 Fax: 610-682-4781 Order Hotline: 610-682-3260